HPEC H4510N PROJECTOR

Display Technology	3 x TFT LCD Panel
Brightness	4500 lm
Resolution	Native : 1024 x768 XGA
	Maximum : 1600x1200 UXGA
	Aspect Ratio : 4 : 3 Native / 16 : 9 Compatible
Lamp Mode	Normal : 330 Watts
	ECO : 264 Watts
Lamp Life	Normal : 2000 HR
	ECO : 3000 HR
Fan Noise	ECO mode 34dB
Projector Lens	Type : Manual Zoom and Focus,
	Zoom Factor : 1.2X
	F-number : 1.7~1.91
	f-number : 24.5~ 28.8mm
Projection Size	40” ~ 300” Diagonal
Projection Method	Front / Rear / Ceiling mount
Throw Distance	1.24~ 11.04m (100” @ 3.7m)
Throw Ratio	1.50 ~1.81
SIGNAL	
Scan Rate	H-Sync Range : 31 to 92 kHz
	V-Sync Range : 48 to 120Hz
Pc Compatibility	VGA, SVGA, XGA, SXGA, WXGA, UXGA
Video Compatibility	NTSC / PAL / SECAM 480i, 480p, 720p, 1080i
Keystone Correction	Auto Keystone Correction, Vertical ±30°
INPUTS/OUTPUTS	
Keystone Correction	Auto Keystone Correction, Vertical ±30°
Output Terminals	RGB : D-Sub 15 pin x 1 Audio : Mini Jack x 1 Mouse Control : USB Type Bx1
Input Terminals	RGB : D-Sub 15 pin x 1, DVI-I x 1 Video : RCA x 1, S-Video x 1 Component Video : RCA x 3 Audio : Mini Jack x 2, RCA(R,L) x 2
Control Terminals	RS -232C: D-Sub 9 pin x 1
LAN	Available
SPEAKER	
	Mono 8 Watts x 1
GENERAL	
Dimensions (W X H X D)	480 x 155 x 365 mm
Net Weight	7.6 kg
Power Supply	100~240 V/AC (Full Range)
Power Consumption	350 Watts
Power Standby	< 5 Watts
STANDARD ACCESSORIES	
	Remote Control (Laser pointer)
	AC power Cord
	VGA Cable, USB Cable
	Owner’s Manual CD
	Quick Start Guide
PECIAL FEATURE	
	Over heat will be shut down automatically
	Auto Vertical Keystone
	Auto Ceiling
	Auto Search

HPEC VIETNAM JSC

www.hpec.com.vn

No.31/76, AnDuong rd.,
TayHo dist.,Hanoi, Vietnam.
TEL: +844-3-7196574
Fax: +844-3-7196575