

ViewSonic® PJ551 Projector

Ultra-Portable XGA Projector



Step up to the PJ551 for higher brightness.

The ViewSonic PJ551 projector offers high performance in an ultra-light 5.4 pound package. Displaying 1,500 lumens and a high contrast ratio, the PJ551 delivers vibrant, rich colors with life-like depth, even in well-lit rooms. True 1024x768 resolution (1280x1024 maximum) produces exceptional image quality for both data and video. Short focal length and zoom let you set up just about anywhere. For performance and value, choose the projector that shines, the ViewSonic PJ551.

ViewSonic has the **best new warranty** and **service support** in the business!



3-Year parts and labor limited warranty

1-Year Free Express Exchange®

1-Year Lamp warranty

And we offer free 24/7[†] technical support for the life of your product, just in case.

High brightness and versatility.

❖ Ideal for mobile professionals.

The PJ551 packs 1,500 lumens in just 5.4 lbs. It's the bright choice for the mobile professional who demands brilliant images in virtually any setting.

❖ Crisp, clear, flexible presentations.

Offering EDTV and HDTV capability, scalable to SXGA resolution, and standard (4:3) and wide-screen (16:9) aspect ratios your images are crisp and clear, your presentation options unlimited.

❖ Whisper-mode extends lamp life and reduces noise output.

Use the whisper-mode function to reduce noise output and extend the life of your lamp up to 4,000 hours*.

❖ The perfect image in any setting.

Use the one-touch setup button and auto tuning to set up quickly, anywhere. Digital keystone correction, short focal length, and zoom function ensure the perfect size image in any meeting environment.

❖ Technical Support wherever, whenever you need it.

Free industry-leading 24/7 customer support,[†] just in case.

❖ The best warranty in the business.

Feel secure knowing you're, covered by a three-year parts and labor limited warranty, first-year Express Exchange® and one-year lamp warranty.**

Super bright



ViewSonic® PJ551 Projector

Ultra-Portable XGA Projector



PJ551 Distance Calculator

Image Size (Diagonal in inches)	Height (in inches)	Width (in inches)	Throw Distance (in inches)
24	14.42	19.12	21.52
48	28.85	38.24	45.04
72	43.28	57.36	68.56
96	57.71	76.48	92.08
120	72.14	95.6	115.6
144	86.57	114.73	139.12
168	101	133.84	162.63
192	115.43	152.97	186.16

Accuracy of the calculations are +/- 5%.
For additional calculations visit ViewSonic.com.

Optional Accessories

Replacement lamp	PRJ-RLC-003
Wall/ceiling mount	PRJ-WMK-001
Hard case with wheels	PRJ-HCH-001
Extended Express Exchange®	EE-LB-02

ULTRA-PORTABLE XGA PROJECTOR

LCD	Type Resolution Pixel Format Lens	3-panel 0.7" TFT active matrix LCD XGA 1024x768 compressed to 1280x1024 1024 horizontal x 768 vertical Manual zoom/focus (manual x 1.2)
DISPLAY	Size Throw Distance Lamp Brightness Contrast Ratio Keystone Correction Aspect Ratio	30"-300" (measured diagonally) 23'-29.5' (.7m-9m) 150W UHB Compact, 4,000* hour rating 1,500 lumens 400:1 ±10 degrees 4:3, 16:9
AUDIO	Speaker	1W monospeaker
INPUT SIGNAL	Video Sync Frequency	RGB analog, NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, PAL 60, SECAM, 480i, 480p, 575i, 720p, 1080i Separated and composite Fh: 15~78kHz; Fv: 56~120Hz
COMPATIBILITY	PC Mac ††	From VGA up to SXGA Up to SXGA (may require Mac adapter)
CONNECTOR	RGB Input Composite Video S-Video Component Audio In	15-pin HD, D-sub (x1) RCA (x1) Mini-Din 4 pin (x1) RCA (x3) RCA (x1)
POWER	Voltage Consumption	100-120V AC / 220-240V AC, 50-60Hz (universal) 210W (typ), 130W (whisper-mode)
USER CONTROLS	Basic Remote OnView®	Standby on/off, menu (left, right, up, down), input, reset, mute, indicator (lamp, power, temp) Standby on/off, video, RGB, menu, position, menu select (left, right, up, down), reset, freeze, magnify (+, -, off), volume (up, down), mute, timer, auto, blank Brightness, contrast, V. position, H. position, H. phase, H. size, color balance (red), color balance (blue), aspect ratio, auto, RGB, keystone, blank, mirror, start up, volume, menu color, timer, language, auto off, sync on green
OPERATING CONDITIONS	Temperature Humidity	32-95° F (0-35° C) 10-85% (non-condensing)
DIMENSIONS	Physical	11.3" x 8.26" x 3.3" 289mm x 210mm x 84mm
WEIGHT	Net Gross	5.4 lbs. (2.5kgs) 13.9 lbs. (6.3 kgs)
REGULATIONS		UL, FCC-B, c-UL, CE, TUV/GS, CB Report, PCT
WARRANTY		Three-year limited warranty on parts and labor, first-year Express Exchange® service, one-year warranty on lamp.**
OTHER		Mirror reverse image, upside down image, digital keystone correction, DDC 1/2B

ISO 9001



FM 40187

ISO 14001



EMS 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



ViewSonic®
See the difference.®

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789
Phone (800) 888-8583 or (909) 444-8888 • In Canada (866) 262-1967 • Fax (909) 839-7922 • SalesInfo@ViewSonic.com • ViewSonic.com

*Running Whisper-mode exclusively can extend lamp life up to 4,000 hours. **Lamp warranty available in U.S. and Canada. Subject to terms and conditions, verification and approval. Applies to manufacturers installed lamp only. All accessory lamps purchased separately are warranted for 90 days. †Excluding major U.S. holidays. †† Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country. See your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2003 ViewSonic Corporation. All rights reserved. [10751-04B-06/03] PJ551-1

For more product information, visit us on the web at ViewSonic.com

specifications