PD721

Display Technology
- DLP™, Digital light processor

Native Resolution
- Native XGA (1,024 x 768)

Compressed Resolution
- SXGA (1,280 x 1,024) compressed

Typical Colors
- 16.7Million Colors

Brightness (ANSI lumens)
- 2,300 ANSI Lumens

Contrast Ratio
- 2000:1

Noise Level
- 32dB

Weight
- 6.6lbs (3Kg)

Dimensions
- 277 x 225 x 85 mm (10.9" x 8.9" x 3.3")

Design Aesthetics
- Two tone black and silver magnuesium body

Computer Compatibility
- IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards SXGA, XGA, SVGA, VGA (resizing)

Video Compatibility
- NTSC M (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i), EDTV (480p), SDTV (480i), 576i/p

Aspect Ratio
- 4:3 Native, 16:9 Compatible

Picture in Picture (PiP)
- Yes

Horizontal Scan Rate:
- 15 ~ 100 kHz

Vertical Scan Rate
- 43 ~ 120 Hz

Projection Distance
- 3.74’ (1.14m) ~ 32.8' (10m)

Projection Screen Size (Diagonal):
- 23" (0.58m) ~ 246" (6.25m)

Keystone Correction
- +/-16 Degrees

Audio
- Yes

Lamp Life
- 2,000 hours

Lamp Type

- 250 W User Replacable UHP Lamp

Power Consumption

- 320 Watts

I/O connectors

- Computer Input: • 1 HDB 15-Pin D-Sub (VGA/Component/HDTV input port) • 1 DVI Connector • 2 Audio Mini Jack (1 for 15-pin
- AV Input: • 1 Mini DIN for S-Video Input Connector • 1 RCA Jack for Composite Video Input Connector • 1 Audio Mini jack for S
- Video Output: • 1 Mini D-SUB 15-Pin for Monitor Loop Through • 1 Remote Mouse Port

Bundled Accesories

- AC Power Cord 15-Pin VGA Signal Cable (1.8 M) RCA Composite/HDTV Video Cable S-Video Signal Cable Wireless Remote
- function and laser pointer AA Type Batteries x 2 for remote multi-language user's guide (CD-ROM) multi-language quick start c
- carrying bag Audio cable jack/RCA Y cable for remote control (support USB/Com port)

Up-grade Options

- Acer Replacement Lamp, External TV tuner