X1161 PROJECTOR

DLP Technology – 3D Ready

Enjoy superb yet budget-friendly projection! The Acer X1161 3D Ready is perfect for home entertainment, SMB or educational settings. Featuring 2500 ANSI Lumens brightness, 4000:1 contrast ratio, and Acer ColorBoost II and Acer SmartFormat technologies, the Acer X1161 3D offers the best price-performance value.

Why X1161 Projector?

- Resolution SVGA (800 x 600), Maximum UXGA (1,600 x 1,200), 1080p (1,920 x 1,080)
- Contrast Ratio 4000:1
- Brightness 2,500 ANSI Lumens (Standard), 2,000 ANSI Lumens (ECO)
- Projection Distance 3.3' (1.0m) ~ 39.0' (11.9m)
- DLP 3D Ready



Lamp Life 4000hrs | Brightness 2500ANSI | Low Noise Level 26 dBA | Resolution SVGA | PICTURE BY DLP TEXAS INSTRUMENTS

Wall-Color Compensation | Keystone Correction 40° | Power Saving ECO Mode | Instant Pack | ColorBoost II

SmartFormat | EcoProjection | empowering technology | Empowering Technology eTimer | Empowering Technology eView

acer
Empowering People

Technical Specification

Model Name	X1161 3D Ready
Resolution	Native SVGA (800 x 600) Maximum UXGA (1,600 x 1,200), 1080p (1,920 x 1,080)
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards 1080p (1,920x1,080), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 (Native), 16:9
Contrast Ratio	4000:1
Displayable Colours	1.07 Billion Colours
Brightness	2,500 ANSI Lumens (Standard), 2,000 ANSI Lumens (ECO)
Projection Lens	F = 2.41 ~ 2.55, f = 21.79mm ~ 23.99mm 1:1.1 Manual Zoom and Manual Focus
Projection Screen Size	23" (58cm) ~ 300" (762cm)
Projection Distance	3.3' (1.0m) ~ 39.0' (11.9m)
Throw Ratio	50"@2m (1.95 ~ 2.15:1)
Horizontal / Vertical Scan Rate	30k ~ 100k Hz / 50 ~ 85 Hz
Lamp Type / Life	Osram 180 W user replaceable P-VIP lamp 4,000 Hours (Standard), 5,000 Hours (ECO)
Keystone Correction	+/-40 Degrees (Vertical), Manual & Auto
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Ceiling Mounting Capability	Yes
Audio	NA
IR Remote Control	IR remote control
Digital Zoom	2X
Power Supply	AC input 100~240V auto-switching power supply
Power Consumption	224 Watts (Operation), <1 Watts (Standby)
Operating Temperature	5℃ ~ 35℃ / 41℉ ~ 95℉
Noise Level	30 dBA (Standard mode), 26 dBA (ECO mode)
Input Interface	Analog RGB/Component Video (D-sub) x 1, Composite Video (RCA) x 1, S-Video (Mini DIN) x1
Output Interface	NA
Control Interface	USB (Type B) x 1
Weight and Dimensions	4.9 lbs (2.2 Kg) / 268 x 192 x 80 mm (10.6" x 7.6" x 3.1")
Compliance	C-Tick (AS/NZS 60950)
Standard Accessories	AC power cord, VGA cable, Composite video cable, Remote control, Battery for remote control, Lens cap, Carrying case, User's guide (CD-ROM), Quick start guide, Security card
Standard Warranty	2 year return to base

Product specifications are subject to change without prior notice. Acer & the Acer logo are registered trademarks of Acer Inc., and Acer America Corp. All other products, brand names, or company names are trademarks & registered trademarks of their respective companies. Acer shall not be liable for technical, editorial or pictorial errors, inaccuracies or omissions contained herein; nor for any consequential damage resulting from the furnishing, performance, or use of this material. * Maximum hours. Actual hours depend on usage and configuration. ** Contact Acer for warranty details.