BOXLIGHT 2015



BRIGHTNESS
3500 ANSI lumens

RESOLUTION
1400 x 1050 true SXGA+
compressed 1600 x 1200 UXGA

DISPLAY TYPE
3 - .99in TFT polysilicon
LCDs with MLA

CONTRAST RATIO
650:1

WEIGHT
17 lbs / 7.7 kg

DIMENSIONS
16.5 x 6.3 x 12.6 in
41.91 x 16 x 32 cm

LAMP
310 watt, UHB

LAMP LIFE
2000 hours

DIAGONAL IMAGE SIZE
40 - 500 in
1.02 - 12.70 m

PROJECTION LENS
power zoom
1:1.5 zoom ratio,
F/1.7 - 2.4, f=31.-46mm

THROW RATIO
1.5 - 2.2 :1

AUDIO
dual 1 watt speakers

Conference room presentations are instantly brighter with the BOXLIGHT 2015 multimedia projector. Featuring 3500 ANSI lumens and 650:1 contrast ratio, this XGA unit is ideal for bright, detailed images in large venues. This well-designed unit includes power lens shift, optional zoom lenses and an easy-to-replace lamp to simplify installations.

Input Panel



Automatic set-up and direct key access for major functions make the BOXLIGHT 2015 easy to use

SPECIAL FEATURES:

650:1 Contrast Ratio
Great definition of image. Blacks and whites enhanced.

Vertical Lens Shift
Create a uniform image on screen in virtually any environment.

Multiple Inputs including RJ - 45
Integrated RJ -45 input for projector control, diagnostics and monitoring over a network.

INPUTS
1 - 15 pin VGA, 1 - M1 - D
1 - BNC, 1 - Composite
1 - S-Video, 1 - Component
2 - Mini jack audio
1 - RJ-45

OUTPUTS
1 - 15 pin VGA
1 - USB mouse
1 - 3.5 Stereo jack audio out

KEYSTONE
Vertical adjustment + / - 15°
Horizontal adjustment + / - 3°

VIDEO
NTSC, NTSC 4.43, PAL, PAL60, PAL-M, PAL-N, 720p SECAM, 480 i/p, 576i,1080i

FCC CERTIFICATION
Class B

DECIBEL RATING
38 dB in whisper mode

POWER SUPPLY
AC100 - 120V, 220-240V
UL Certified

SHIPS WITH:

- Remote control
- Lens cap
- Composite AV cable
- Power cord
- RGB cable
- M1-D cable
- User Manual

WARRANTY:
Two year parts and labor (120-day/500hour lamp guarantee)

BOXLIGHT®
Presenting a Better Way

19302 Powder Hill Place, Suite 101
Poulsbo, WA 98370

www.boxlight.com
Direct - 800.762.5757
International - 360.779.7901
Partners - 866.688.3636

2006 BOXLIGHT Corporation. All rights reserved. Specifications are subject to change without notice