# Pocket DLP Projector

## PD2100

COMMITTED TO XCELLENCE



SVGA 800x600

<1.2 lbs WEIGHT

1000:1 CONTRAST

| | |
|---|---|
| **Light Value** | Single 0.55" 12° DDR DMD ™ panel |
| **Resolution** | Native: SVGA (800 x 600)<br>Maximum Support: SXGA (1280x1024@60Hz) |
| **Brightness** | •Typical 360 Lux at 15" screen size (25 lumens) as High Brightness Mode on<br>•Typical 288 Lux at 15" screen size (20 lumens) as standard Mode |
| **Brightness Uniformity (JBMA)** | Typical 85% |
| **Contrast Ratio (Full On/Off)** | 1000:1 |
| **Light source** | Osram OSTAR LED module |
| **LED life time** | Typical 5000 hours |
| **Displayable Color** | 1.67 million |
| **Projection Lens** | Fixed zoom with focus adjustment: F2.0 |
| **Projection Range** | Image size: 12" ~ 60"<br>Distance: 40cm ~ 20cm |
| **Performance Range** | Image Size: 15" ~ 50"<br>Distance 48cm ~ 167 cm |
| **Power Consumption** | Operation: < 30W in standard mode<br>Standby: DC 0.3W AC: 4W |
| **Dimension (W x D x H)** | 121 x 99 x 47 mm |
| **Weight** | < 1.2 lbs |
| **I/O Connectors (Standard)** | •DC power input jack<br>•RCA jack for composite video input<br>•S-Video input (4 pin Mini DIN)<br>•D-SUB 15 female for analog VGA input |