

PS-5120

HIGH PERFORMANCE, LOW COST HOME CINEMA PROJECTOR

Designed to bring affordable pricing to home cinema entertainment, the PS-5120 offers the benefits of 1200 ANSI lumens brightness and a 400:1 contrast ratio that means great pictures anywhere indoors. The PS-5120 offers a native resolution of 800 x 600 (SVGA) and includes digital keystones to ensure perfectly shaped pictures even when projecting at close range, regardless of the angle. It offers a colour depth of 16,7 million and a wide range of connectivity options: C-video, S-video and YcbCr. Its stylish silver; lightweight (3,1 kg) casing and matching remote control with laser pointer and trackball mouse complete the package.

Display Device	0.7" Poly-Silicon TFT-LCD x 3
Native Pixel No.	800 x 600 (SVGA)
ANSI Lumens	1200 ANSI
Contrast Ratio	400:1
Color Depth	16,7 M
Uniformity	85 %
Aspect Ratio	4:3, 16:9
Compatible Mode	SXGA, XGA, SVGA, VGA, MAC
Max. Display Mode	1280 x 1024 @ 60Hz
H Frequency	15 ~ 90 KHz
V Frequency	43 ~ 85Hz
Image Size Diagonal	40" ~ 200"
Projection Distance	1,33 m ~ 8,33 m
Zoom	Manual
Focus	Manual
Lamp Power	150 W EHPL Lamp
Lamp Life Time	2.000 Hrs
Operating Power Consumption	210 W
Standby Power Consumption	6 W
Digital Zoom	x1~x16, 20 steps
Digital Keystone	+/-15 deg
PC Signal Input	D-15 Female x 1
Monitor Output	No
Video Input	RCA (C-Video) x 1, Mini-Din (S-Video) x 1
Audio Input	No
Audio Output	No
Control I/O	No
Power Input	3 Pins Jack
RGB Input Video Signal	RGB, max 1.0 Vpp 75 ohms
RGB Input Sync Signal	Separate H/V, Composite SOG
RGB Output Video Signal	No
RGB Output Sync Signal	No
Video Standard Input	NTSC / PAL / SECAM
Picture in Picture	Video on Computer
Plug & Play	DDC Plug & Play
Projection Methods	Front, Rear, Ceiling, Ceiling + Rear Projection
Dimension	297 x 233 x 93 mm
Net / Gross Weight kg	3,1 Kg
Noise	< 36 dB
Accessory	
	Hand Carry Bag (Option)
	Remote Controller
	VGA Cable
	AV Cable
	S-Video Cable
	Component Cable
	PS-2 Mouse Cable
	Lens Cap
	Power Cord
	AAA Battery
	User's Manual
Regulation	
EMI	FCC–B, CE (Class B)
Safety	UL, CE

SEE MORE DETAILS

CTX

COMMITTED TO XCELLENCE

www.ctxeurope.com