easyview



easyview

Keep it real.

Technical Data easyview



Model	PX770	PX721w	PX621
Easyview			
Display Type	0.7" XGA DDR DMD	0.65 WXGA DDR DMD	0.55 XGA/SVGA DDR DMD
Resolution (Native Pixels)	XGA (1024 x 768)	WXGA (1280 x 768)	XGA (1024 x 768) SVGA (800 x 600)
Brightness (ANSI Lumens)	1800	1500	2000
Uniformity	80%	85%	80%
Lens	Manual Zoom (1.16x)	Manual Zoom (1.12X)	Manual Zoom (1.2x)
Contrast ratio	2000:1	2000:1	2000:1
Screen Size	40 ~ 273 Inches	37.5 - 250 inches	31.2 ~ 312 Inches 27.8 - 277.7 inches
Lamp	150W	230W	205W
Lamp Life	3000 hours	2000 Hours	2000 hours
Color Wheel	4 Segment RGBW	6 Segment	4 Segment RGBW
Keystone Correction	Vertical: +/- 15 degrees	Vertical: +/- 15 degrees	Vertical: +/- 15 degrees
Audio System	1W x 1	2W x 1	2W x 1
Video Signals	NTSC PAL - 60, M, N, B, D, G, H, I SECAM	NTSC PAL - 60, M, N, B, D, G, H, I SECAM	NTSC PAL - 60, M, N, B, D, G, H, I SECAM
Computer Input	D-Sub 15 pin	D-Sub 15 pin	D-Sub 15 pin
Computer Output	NA	NA	D-Sub 15 pin
Video Input	S-Video, Composite Video, D-sub	S-Video, Composite Video, D-sub,HDMI	S-Video, Composite Video, D-sub
Audio Input	Mini Jack	Mini Jack	Mini Jack
Control Input	USB, RS232	USB, RS232	USB, RS232
Sound Noise	34dBA	33dBA	34dBA
Power Requirement	100 - 220v, 50 - 60Hz	100 - 240v, 50 - 60Hz	100 - 240v, 50 - 60Hz
Power Consumption	200W	280W	250W
Dimension (WxDxH)	201 x 155 x 58 mm	106 x 287 x 220.5 mm	265 x 202 x 97 mm
Weight	1.18Kg	3 Kg	2.4Kg
Standard Accessory	Remote Control with 2 batteries	Remote Control with 2 batteries	Remote Control with 2 batteries
	Power cable x 1	Power cable x 1	Power cable x 1
	D-Sub to D-sub cable x 1	D-Sub to D-sub cable x 1	D-Sub to D-sub cable x 1
	Audio cable x 1 / S-video x 1	Audio cable x 1 / S-video x 1	Audio cable x 1 / S-video x 1
	Composite video x 1	Composite video x 1	Composite video x 1
	Operating manual x 1	Operating manual x 1	Operating manual x 1
	Carrying bag x 1	Carrying bag x 1	Carrying bag x 1

Technical changes and mistakes reserve!