PORTABLE PROJECTOR

SPECIFICATIONS **Professional**



Feature

1. Customised startup logo with capture Screen
2. On Start Function
3. Image zoom out/in
4. Anit-Thief /Triple password Protection
5. Image Freezing, Zoom & Panning
6. Auto Power-Off on Singal Sourcing Failure
7. Support : 1 computer to display up to 200 Projector
8. Support : 4 computer to display to Projector at the same time
9. wireless support with wifi dongle

Remote Control (Card Type)

Description	B40	B50
Display Technology	Liquid Crystal Display	
Display Panel	0.63" x 3" LCD Panel	
Brightness (ANSL Lumens)	4,000	5,000
Native Resolution	XGA (1024x768)	
Contras Ratio	10000:1 with IRIS and ECO	
Projection Lens	F=1.6-1.76, f=19.158-23.018 mm, Zoom Ratio 1.2X Screen 30-300 Wide	
Uniformity	80%	
Throw Ratio	70"@2.1m (1.48~1.78 : 1)	
Throw Distance	1.48 (wide)-- 1.78 (tele)	
Aspect Ratio	4:3 (Native), 16:9 (compatible)	
Keystone Correction	Keystone V: ± 30° H: ± 15°, pincushion, Barrel, corner :± 40°	
I/O Port		
- Computer (input)	D-sub 15pin, (VGA) x2	
- Computer (output)	VGA D-sub 15pin share with VGA in	
- C-video	x1	
- S- Video (input)	share with VGA in	
- Mini Jack audio (Input)	3.5mm x1	
- Mini Jack audio (Output)	3.5mm x1	
- Audio L/R (Input)	RCA (L/R) x2	
- RS232	9pin x 1	
- USB A	x 1 Display (Support picture , .pdf and .avi Movies)	
- USB B	x 1 Display from Computer	
- RJ45	x 1 Control and Display from computer	
- HDMI	x 2 (1 is Compatible with MHL)	
PC Compatibility	VGA, SVGA, XGA, SXGA,WXGA,UXGA,WUXGA,Mac	
Video Compatibility	PAL,SECAM,NTSC 4.43,PAL-M, PAL-N, 480i,480p,576i,576p,720p,and 1080p	
Option	wireless support with wifi dongle	
Speaker	10watt	
Lamp	218Watt	
Lamp Life (Nomnal / Economic)	4000Hrs/10000Hrs	
H-Synch Range	15~100KHz	
V-Synch Range	48~85Hz	
Power Consumption	270 Watt	
Power Supply	100~240V@ 50/60Hz	
Warranty	1 year, Lamp 1 year or 1,000 hrs whichever comes first	