CP-X2010N series

HITACHI
Inspire the Next

My Image / *Campus Notification System* | Closed Captioning | AMX Device Discovery



Key Features

- 2,200 ANSI Lumens
- Native XGA Resolution
- 500:1 Contrast Ratio
- 8.8 lbs.
- 2 RGB Inputs / 1 RGB Output
- Component / Composite / S-Video Inputs
- 16 Watt Audio Output
- Network Control, Maintenance, & Security
- Network Bridge (RS-232 Pass Through)
- Approx. 6,000 Hours (Eco Mode)*
- Security Bar & Transition Detector
- 29 dBA (Eco Mode)
- Easily Accessible Hybrid Filter (5,000 Hours between maintenance)
- PJ Setup
- Network Messenger
- Audio Pass Through
- Template Function
- Power Saving Mode



Screen Size 4:3 Throw Distance

Diagonal*	Width*	Min*	Max*
30	24	34	41
60	48	70	83
80	64	94	112
100	80	118	140
120	96	142	168
150	120	177	211
200	160	237	281
300	240	356	422

Throw Ratio: 1.5 - 1.8:1 (distance : width)
*Measured in inches

Specifications

Model Name		CP-X2010N Series
Liquid Crystal Panel Structure		0.63" Polysilicon Active-matrix TFT x 3
Number of Pixels		786,432 Pixels
Resolution	Video	540 TV lines
	RGB	1024 dots x 768 lines
Colors		16.7 million colors
Aspect Ratio		Native 4:3 / 16:9 compatible
Lens		manual zoom x 1.2
Throw Ratio (distance : width)		1.5 - 1.8 : 1
Lamp		210W UHP
Brightness		2,200 ANSI lumens
Expected lamp Life		Approximately 3,000 hours (normal) 6,000 hours (Eco mode)*
Contrast Ratio		500 : 1
Speaker Output		16W (2 speakers)
Power Supply		AC100 - 120V / AC220 - 240V 50/60 Hz Power
Power Consumption		330W
Operating Temperature		5˚C - 35˚C (41˚F - 95˚F)
Input Signals	RGB	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, MAC13", MAC16"
	Composite Video	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N
	Component Video	480i, 576i, 480p, 720p, 1080i, 1080p
Acoustic Noise Level		35 dBA (29 dBA in Eco mode)
H-Sync		15 kHz - 106 kHz
V-Sync		50 kHz - 120 kHz
Vertical Keystone		+ / - 30˚
Approvals		UL, C-UL, FCC, CE, RoHS
RGB Input	Analog RGB	15-pin D-sub connector x 2
RGB Output	RGB	15-pin D-sub connector x 1
Video Input	S-Video	Mini DIN 4-pin connector x 1
	Composite Video	RCA jack x 1
	Component Video	RCA jack x 3
Audio	Input	Stereo mini jack x 2, RCA (L/R) x 1 pair
	Output	RCA (L/R) x 1 pair
Ethernet		RJ-45 port / 100 base-T
Control Terminals		9-pin D-sub connector x 1 (RS-232 control)
Other		USB connector (USB mouse) x 1
Dimensions (W x D x H)		12.5" x 11.3" x 4.6"
Weight		8.8 lbs.
Closed Caption		CC1, CC2, CC3, CC4, T1, T2, T3, T4
Additional Features		Kensington Slot, Digital Gamma Correction, Whiteboard / Blackboard Mode, Input Source Naming, MyMemory / MyScreen / MyButtons / MyText, Auto V Keystone, Serial Number on Side
Supplied Accessories		Remote Control, Batteries (AA), RGB cable, US Power Cord, Multiple language operator / Safety Manual
Lamp		CPX2010LAMP (DT01021)
Remote Control		HL02483
Filter		MU06481



* Actual lamp life will vary by individual lamp and based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.

For sales information, please call 800.225.1741
Printed 04.09

All specifications subject to change without notice