# CP-X2011N

HITACHI
Inspire the Next

AMX Device Discovery | Closed Captioning | Crestron Integrated Partner

## Key Features

- 2,200 ANSI Lumens
- Native XGA Resolution
- 500:1 Contrast Ratio
- 7.9 lbs.
- Microphone input with amplifier
- Network control, maintenance and security
- Network Bridge RS232 control
- Lamp life approximately 6,000 Hours (Eco Mode)*
- HDMI / Component / Composite / S-Video Inputs
- Stand-by Audio
- 16W Speaker Output
- 0.5 watt power saving mode using 120V
- Template Function
- 2 RGB In, 1 RGB out / Composite / S-Video
- USB connection to computer
- PC-less presentation
- Network Messenger
- Present content via LAN
- 29 dB (Eco Mode)
- Stand-by Audio






Screen Size 4:3 Throw Distance

| Diagonal* | Width* | Min* | Max* |
|---|---|---|---|
| 30 | 24 | 34 | 41 |
| 60 | 48 | 70 | 83 |
| 80 | 64 | 94 | 112 |
| 100 | 80 | 118 | 140 |
| 120 | 96 | 142 | 168 |
| 150 | 120 | 177 | 211 |
| 200 | 160 | 237 | 281 |
| 300 | 240 | 356 | 422 |

Throw Ratio: 1.5 - 1.8:1 (distance : width)
*Measured in inches

## Specifications

| | | |
|---|---|---|
| Model Name | | CP-X2011N Series |
| Liquid Crystal Panel Structure | | 0.63" polysilicon active-matrix TFT x 3 |
| Number of Pixels | | 786,432 pixels |
| Resolution | Video | 540 TV lines |
| | RGB | 1024 dots X 768 lines |
| Colors | | 16.7 million colors |
| Aspect Ratio | | Native 4:3/16:9 compatible |
| Lens | | manual zoom x 1.2 |
| Throw Ratio (distance : width) | | 1.5 - 1.8 : 1 |
| Lamp | | 190W UHB |
| Brightness | | 2,200 ANSI Lumens |
| Expected lamp Life | | Approximately 3,000 hours (normal) 6,000 hours (Eco mode)* |
| Contrast Ratio | | 500 : 1 |
| Speaker Output | | 16W (2 x 8W speakers) |
| Power Supply | | AC100 - 120V / AC220 - 240V 50/60 Hz Power |
| Power Consumption | | 330W |
| Operating Temperature | | 5℃ - 35℃ (41℉ - 95℉) |
| Input Signals | RGB | VGA, SVGA, XGA,SXGA, SXGA+, UXGA, MAC 13", MAC 16" |
| | Composite Video | NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N |
| | Component Video | 480i, 576i, 480p, 720p, 1080i, 1080p |
| Acoustic Noise Level | | 35 dB (29 dB in Eco Mode) |
| H-Sync | | 15 Hz - 106 Hz |
| V-Sync | | 50 kHz - 120 kHz |
| Vertical Keystone | | + / - 30˚ |
| Approvals | | UL, C-UL, FCC, CE, RoHS |
| RGB Input | Analog RGB | 15pin Mini-Dsub x 2 |
| RGB Output | RGB | 15pin Mini-Dsub x 1 |
| Digital Input | | HDMI x 1 |
| Video Input | S-Video | Mini DIN 4-pin connector x 1 |
| | Composite Video | RCA jack x 1 |
| | Component Video | RCA jack x 3 |
| Audio | Input | Stereo Mini jack x 2, RCA(L/R) x 1 pair, Microphone Jack(stereo mini) x 1 |
| | Output | RCA(L/R) x 1 pair |
| Ethernet | | RJ-45 port / 100 base-T |
| Control Terminals | | 9-pin D-sub connector x 1 (RS-232 control) |
| Other | | USB-A, USB-B (USB Mouse) |
| Dimensions (W x D x H) | | 12.5" x 3.9" x 11.3" |
| Weight | | 7.9 lbs. |
| Closed Caption | | CC1, CC2, CC3, CC4. T1, T2, T3, T4 |
| Additional Features | | Kensington Slot, Digital Gamma Correction, Whiteboard / Blackboard More, Input Source Naming,, MyMemory / MyScreen / MyButtons / MyText, Auto V Keystone, Serial Number on Side |
| Supplied Accessories | | Remote Control, Batteries (AA), RGB cable, US Power Cord, Multiple language operator / Safety Manual |
| Lamp | | CPX2010LAMP (DT01021) |
| Remote Control | | HL02483 |
| Filter | | MU06481 |





All specifications subject to change without notice