

iRULU GP90



iRULU GP90



Display Type	 1 x 5,8" LCD TFT Panel WXGA 16/10 Liquid Crystal Display	
Ansi-Lumen	-	Lux (bei 200 cm Screen)
Contrast	3000:1	-
Black Level	-	-
Offset	-	-
Resolution	WXGA 1280 x 800 1.024.000 Pixel	
Video Modes	Pal, SECAM, NTSC, HDTV 720p, 1080i, 1080p, EDTV 480p, 576p	
Application	Standard-Portabel External training and company presentations, as well as product presentations. Very narrow picture width and rooms with very little light.	
Light Source	LED	
Light Life	20000 h.	
Operating Costs	0,00 € LED	
Focus	Manual	
Zoom	-	
Objective	-	
Throw Ratio	-	
Audio	5W	
Connections	2x USB 2x HDMI in TV AV YPBPR D-Sub 15 pin in Audio in and out	
Ceiling Mounting	Yes	
Power	110W	
Size WxHxD	284,5 x 114,3 x 228,6 mm (11,2"x4,5"x9") 7,38 L/dm³	
Operating Noise	28dB	
Weight	2,18 kg / 4,81 lbs.	
Keystone	Vert.: +/-15°	
Illumination	-	
Frequenz	-	
Foot-Lamberts	-	
Features	Full HD 1080P compatible 360° installable Android 4.4 OS 1GB RAM 8GB ROM	

More Details



HCinema

<https://www.projector-database.com/pro/iRULUGP90-en.html>

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.