



Practical, Advanced, Abundant Features



High Brightness & Contrast Ratio

The PCL-LT114X, PCL-LT115X, PCL-LT113W carry from 4000 to 4500 ANSI lumens, 15000:1 to 16000:1 contrast ratios, for vivid image quality and clear details on projected images.



MHL Compatible - Easy Connectivity

Easy connection to a laptop, PC, games console or DVD player with HDMI. It is MHL compatible allowing to connect any MHL enabled mobile devices with a single cable solution to mirror your devices screen. Ideal for streaming movies and viewing files and photos stored on your mobile devices.



Wireless Presentation Compatible

Connect the projector to a computer or your network using the optional USB wireless adapter. The adapter supports IEEE802.11n.



Network Control

With a wired connection via RJ45, control or monitor all projectors through corresponding IP. Turn the projectors on/off, check configurations, view lamp using times and operational status through the network.



Easy Lamp Replacement

The lamp cover is conveniently located on the top of the projector for easy replacement, even when the projector is installed on the ceiling.



V / H Keystone Correction / Corner Keystone

Horizontal and vertical digital keystone correction fixes image distortion created when a projector's lens is not perpendicular to the screen. Corner keystone correction allows the adjustment of all four angles of the image. These are ideal tools for when the projection environment is less than ideal.



1.2x Standard Digital Zoom Lens

The PCL-LT114X, PCL-LT115X, PCL-LT113W projectors feature a 1.2x zoom lens for better image quality through the enlarged pixels. This allows the projector to be placed in various areas to meet installation requirements with the larger projected picture.



USB Display, Memory Viewer

USB Display outputs images and sounds from computers without installing any software, simply connect to the USB port with a single USB cable and start your presentation. In addition to JPG/BMP images and text files, PDF files can be projected by simply inserting a USB memory device.

Specifications

Model	PCL-LT114X	PCL-LT115X	PCL-LT113W
Display Technology	Liquid Crystal Display		
Display Panel	3 x 0.63"	3 x 0.63"	3 x 0.59"
Brightness	4200 ANSI Lumens	4500 ANSI Lumens	4000 ANSI Lumens
Native Resolution	XGA (1024 x 768)	XGA (1024 x 768)	WXGA (1280 x 800)
Contrast Ratio	16000:1	15000:1	15000:1
Throw Ratio	Min Zoom: 1.48 - Max Zoom: 1.78		
Projector Lens	1.2x F=1.6 - 1.76, f=19.158 - 23.018mm		
Uniformity	90%		
Distance / Screen Size (Diagonal)	0.9m - 11.0m (30" - 300")		0.95m - 11.6m (30" - 300")
Aspect Ratio	4:3 (Standard), 16:9 (Compatible)		16:10 (Standard), 4:3 (Compatible)
Keystone	V: ±30° (Auto/Manual) H: ±15° (Manual), Pincushion/Barrel Correction, Corner Keystone		
Input	1-HDMI in (MHL, 1-HDMI), Audio: 3.5 Mini-Jack, Video, 2-VGA, YCbCr/Component/S-Video (Share with VGA in 1) USB-A (Support memory viewer/optional Wifi dongle) 2-Audio-In (L/R), USB-B (Display), RJ45 (Display)		
Output	VGA (Share with VGA in 2), Audio Out		
Control	RS232, RJ45, USB-B (FW upgrade)		
PC Compatibility	VGA, SVGA, XGA, SXGA, WXGA, UXGA, WUXGA, Mac		
Video Compatibility	PAL, SECAM, NTSC 4.43, PAL-M, PAL-N, 480i, 480p, 576i, 576p, 720p, 1080p and 1080i		
Lens Shift H.	N/A		
Lens Shift V.	N/A		
Lamp	230 Watts (Philips)	240 Watts (Philips)	230 Watts (Philips)
Lamp Life	(STD Mode) 6000 hours, (ECO Mode) 10000 hours		
Lamp Replacement	Top Lamp Replacement		
Remote Control	Yes		
H. Synch Freq.	15K - 100KHz		
V. Synch Freq.	48 - 85Hz		
Standby Power	< 0.5 Watts		
Power Consumption	Max 270 Watts		
Power Supply	100V - 240V @ 50 - 60Hz		
Operating Temp.	0°C - 40°C (Over 35°C Go to ECO Mode)		
Storage Temp.	-20°C - 60°C		
OSD Languages	26 languages: English, German, French, Italian, Spanish, Polish, Swedish, Dutch, Portuguese, Japanese, Simplified Chinese, Traditional Chinese, Korean, Russian, Arabic, Turkish, Finnish, Norwegian, Danish, Indonesian, Hungarian, Czech, Kazak, Vietnamese, Thai, Persian		
Speaker	10 Watts		
Dimensions	34.7cm x 25.7cm x 10.9cm (13.6" x 10.1" x 4.3")		
Weight	3.2Kg (7.0Lbs)		
Standard Accessories	User Manual (CD), Power Cord, Remote Control, VGA Cable		
Other Features	1. One Touch Lamp Replacement 2. Quick Power Off 3. Customized Startup Logo 4. Auto Image Reverse*	5. Build in Test Images 6. Corner Keystone* 7. Powerful 10 Watts Speaker* 8. HDMI Compatible with MHL*	9. LAN Display* 10. PC Less Presentation* 11. Mirror Display with iOS/Android Devices Via USB Adapter*

*: applied on selected models only.



Note: I/O Ports shown here are specifically for PCL-LT114X/PCL-LT115X/PCL-LT113W.

Make an impact with powerful impressions and effective solutions.

For more information, email info@infotodisplay.com or visit www.infotodisplay.com.

© INFOTO 2015 - 2016. All rights reserved. INFOTO logo is a registered trademark of INFOTO Display. All specifications are subject to change without prior notice.



*MHL, "AMX", "Crestron" and "PLink" are registered trademarks of their respective owners in United States and/or other countries.