JAVES
Projector & Screen

Educational Type DLP Projector

HD-520 Series

Cost-Effective, Portable, Compact
SVGA / XGA Resolution
2200 ANSI Lumen

• **Model**	HDS-520 / HDX-520
• **Light Valve**	Single 0.55" DLP panel(Type-X)
• **Brightness**	2200 Lumen
• **Contrast Ratio**	2000:1
• **Lamp**	OSRAM 180W E20.6 lamp
• **Number of Pixels**	SVGA (800 x 600) / XGA (1024 x 768)
• **Displayable Color**	1073 million; 30-bit color
• **Color Wheel**	4 Segment RGBW, 120Hz(2X)
• **Projection Lens**	1.1X manual zoom
• **Projection Screen Size**	25-250"
• **Projection Distance**	1-10m
• **Video Compatibility**	NTSC, NTSC 4.43, PAL, PAL-N, PAL M, SECAM and HDTV (480P; 576P, 720P; 1080i) compatible, Composite video, and S-video capability
• **H. Frequency**	15kHz-100kHz horizontal scan
• **V. Frequency**	43Hz-120Hz vertical refresh
• **Power Supply**	Universal 90–240V AC 50–60 Hz with PFC input
• **Power Consumption**	230W
• **Audio**	1 x 2W
• **Noise Level**	34dBA
• **Weight**	2.7 Kg
• **Dimensions (W x H x D)**	271 x 218 x 85 mm
• **Environmental**	Operating temperature: 5°C–35°C (41°F–95°F) Humidity: 80% maximum Storage temperature: –20oC to 60oC (–4oF to 140oF) Humidity: 80% maximum
• **I/O Connectors**	Input: 2 x RGB, S-video, Composite, RS232 Output: RGB

JAVES PROJECTOR

Address: Room 207, Block B, Seaview Estate, Watson Road, North Point, Hong Kong
Tel:(852) 2887-5151 e-mail: jng@javesprojector.com Web-site: www.javesprojector.com