



KINDERMANN KX 5000 NL

The reliable projector for permanent installation

- Highly efficient filter system (optional, against dust and smoke)
- Quick power on/off
- Low fan noise (29 dB in eco mode)
- Network integration (system check and control)
- Antitheft device through password protection and safety rod
- Supplied **without lens**

Technical data

KX 5000 NL	
Ref. No.	8757-20
Resolution	1024 x 768
Lumens (ANSI)	4500
Contrast ratio	500:1
Noise level approx.	32 dB (Eco 29 dB)
Dimensions	480 x 152 x 360 mm
Weight (w/o lens)	3.3 kg

Optional interchangeable lenses – for different room sizes

Model	F-number	Focal length	Zoom	Distance	Diagonal	Ratio	Ref. No.
ELS-01	1.7–1.99	f= 28.8–36.6 mm	1.27 fach	2–20 m	1.5–12 m	1.8–2.3	No. 8708-0
ELS-02	1.77–2.2	f= 36.5–45.8 mm	1.25 fach	3–25 m	1.5–12 m	2.3–2.9	No. 8708-1
ELS-03	1.8–2.1	f= 51.0–64.3 mm	1.26 fach	3–30 m	1.5–12 m	3.1–4.1	No. 8708-2

Easy mounting with 4 screws

Easy change of lamp and air filter, even if unit is mounted on the ceiling



High connectivity

