



Kindermann KX 6000W

The installation projector with high flexibility

Light output 5200 lumens (ANSI)

Resolution WXGA (1280 x 800)

Low noise level 30 dBA / ECO

- High connectivity, e. g. 2 x VGA, 3 x HDMI, 1 x displayport, 5 x BNC
- Interchangeable lenses, compatible with Panasonic models of EX- and EW-series
- Display also possible via WLAN/LAN/USB
- Lens shift, vertical and horizontal
- Autofocus
- Integrated 10 W loudspeaker

TECHNICAL DATA	Kindermann KX 6000W
Ref. No.	3000 000 760
Native resolution (pixels)	WXGA (1280 x 800)
Supported resolutions	VGA - UXGA / up to 1080p
Lumens	5200
Display type	LCD
Contrast ratio	1000 : 1
Frequency: horizontal, vertical	15 - 100 kHz, 48 - 120 Hz
Focal length in mm	21.3 - 34.16
Image diagonal in m	0.76 - 7.62
Projection distance in m	0.8 - 13.6
Ratio (distance : image width)	1.3 - 2.1 : 1
U/D-Ratio/Offset	Lensshift h50%, v10% / max.
Interchangeable lenses	yes
Lamp	275 W USHIO
Noise level	30 dB eco
Dimension in mm (BxHxT)	410 x 165 x 425
Weight in kg	8.8
INPUTS / OUTPUTS	
Computer VGA (analogue)	2 x HD15, 1 x BNC/5
DVI/HDMI (digital)	1 x DVI-D, 3 x HDMI, 1 x DP
Video	1 x Cinch
S-Video	1 x 4-pin MiniDIN
Component Video	1 x Cinch/ x 3
RS232 interface	1 x RS232 (9-pin)
LAN control	1 x LAN/RJ45
Mouse interface	-
USB	yes, 1 x USB/B
Audio (computer)	1 x stereo jack
Audio (video)	1 x Cinch/ x 2
Monitor output	yes (variable in/out)
Audio output	yes
FEATURES	
Keystone correction (digital)	vert. & hor. $\pm 30^\circ$, manual
Loudspeaker	1 x 10 W
Presentation via LAN/WLAN	yes/yes
Presentation from memory medium	yes, 1 x USB/A
Safety features	Password protection, security bar
Laser pointer in IR remote control	no
Voltage	100 - 240 V AC, 50 - 60 Hz
Special features	Lens shift, high connectivity
Lamp warranty	3 years or 1000 hours (whatever comes first)
Warranty (bring-in)	3 years in Europe, 2 years outside Europe
Package includes	Standard lens, IR remote control, power supply, VGA cable, operating instructions (CD)

