

dv 500

State-of-the-art projection technology

Liesegang

projection technology



dv 500 – high-tech for your conference room

With a level of equipment that leaves no wish unfulfilled, the **dv 500** is on a top position among conference room projectors. Countless connection possibilities, automatic vertical keystone correction and the motorised zoom lens underline the professional aspirations of the **dv 500** as much as its high luminous power of 3,500 ANSI-lumens. An optionally available wireless module enables the **dv 500** to be connected to a network and allows **wireless** transmission of the video signal to the projector. Presentation without limits – the **dv 500** sets new standards.

dv 500




dv 500

State-of-the-art projection technology

Liesegang

projection technology



- HDTV compatible
- Motorised zoom lens
- Automatic vertical keystone correction, horizontal keystone correction
- Optimum video representation using Progressive Scan
- IR remote control with mouse function and laser pointer
- Integrated presentation tools: digital zoom, picture-in-picture, freeze frame
- Individually programmable starting image
- PIN lock against unauthorised usage
- Electronic image reversal for back projection and projection from the ceiling



Liesegang dv 500

0289 046C 0000

including power cord, connecting cables,
remote control, user manual, software
EAN 4043822289013

Accessories

275 W Spare lamp

ZU 0289 04 4010

Ceiling mounting

ZU 0265 75 0009

Kensington Lock™ Anti-theft device

ZU 0266 78 0000

Technical Specifications*	dv 500
Technology	3 x 0.99" LCD
Native resolution	XGA, 1,024 x 768 pixel
Supported resolution	up to UXGA
Video compatibility	PAL, SECAM, NTSC, HDTV
Contrast ratio	800:1
Brightness standard mode	3,500 ANSI lumens
Brightness whisper mode	2,800 ANSI lumens
Lamp, Lifetime**	275 W UHB, 2,000 h
Mains voltage	100–120 VAC / 220–240 VAC, 50–60 Hz
Power consumption	430 W / 10 W stand-by
Dimensions (W x H x D)	390 x 120 x 290 mm (15.4" x 4.7" x 11.4")
Weight	5.7 kg (12.6 lbs)
Keystone correction	± 5° hor. / ± 15° vert.
Scanning frequency hor. / vert.	15–91 kHz / 50–120 Hz
Pixel clock	120 MHz
Image uniformity	85 %
Speaker	2 x 1 W
Projection lens	F = 1.7–2.4, f = 30.5–45.8 mm
	1.5 x Power zoom and Focus
Digital Zoom	4 x
Projection distance	0.9–9.3 m (Wide), 1.3–13.9 m (Tele)
Screen size (diagonal)	0.77–7.70 m (30"–300")
Throw ratio	1.5–2.26
Noise level	39 dB standard mode, 35 dB whisper mode
Connectors	
Computer in	2 x RGB analog (D-Sub HD), 1 x DVI-D
	5 x BNC
Mouse	1 x USB
Control	1 x RS-232
Monitor out	1 x RGB (D-Sub HD)
Video in	1 x Video (Cinch)
	1 x S-Video (Mini-DIN)
	1 x Component (Cinch)
	1 x Component (BNC)
Audio in	1 x Audio Stereo (Cinch)
	2 x Audio Stereo (Mini jack)
Audio out	1 x Audio Stereo (Cinch)
Approvals	CE, FCC B, UL, TÜV
Miscellaneous specifications	
	• Automatic signal detection
	• Multilingual on-screen menu
	• Suitable for 4:3 and 16:9 aspect ratio

* Subject to modification, ** Average lifetime

Distance in m (inch)	Image Size in m (inch)		Image diagonal in m (inch)	
	from	to	from	to
1.5 (59.1")	0.66 (26.13")	1.00 (39.37")	0.83 (32.66")	1.25 (49.21")
2.0 (78.7")	0.88 (34.84")	1.33 (52.49")	1.11 (43.55")	1.67 (65.62")
2.5 (98.4")	1.11 (43.55")	1.67 (65.62")	1.38 (54.44")	2.08 (82.02")
3.0 (118.1")	1.33 (52.26")	2.00 (78.74")	1.66 (65.33")	2.50 (98.43")
5.0 (196.9")	2.21 (87.10")	3.33 (131.23")	2.77 (108.88")	4.17 (164.04")
7.0 (275.6")	3.10 (121.94")	4.67 (183.73")	3.87 (152.43")	5.83 (229.66")

Liesegang Optoelectronics GmbH
Kaistrasse 5
40221 Duesseldorf
Germany
phone +49 (0) 2 11/39 01-1
fax +49 (0) 2 11/39 01-227
www.liesegang.com
info@liesegang.com

Liesegang Corp.
1001 W. Cypress Creek Rd. 103
Ft. Lauderdale, FL 33309
USA
phone (954) 489 23 01
fax (954) 489 23 18
www.liesegangcorp.com
info@liesegangcorp.com

Your Liesegang specialist dealer