



EP747 DLP™ DIGITAL PROJECTOR



- **3000 ANSI Lumens XGA**
- **2200:1 contrast**
- **Superb Connectivity**
- **Elegant, low-noise Design**
- **3000 Hr Lamp Life**

- **Super-bright business projector with excellent Video performance.**
- **Ideal for installation but small and stylish enough for portable use.**
- **Easy to control with full function remote-mouse and RS232.**
- **Four audio inputs and five video inputs.**

Product Highlights

Native Resolution DMD Type Contrast Brightness Lamp Hours/Power Accoustic Noise Aspect Ratio Throw Ratio Offset Optical Zoom Proj. Distance Keystone Corr. Weight Dimensions Power	1024 x 768 (XGA) DLP™ 0.7 DDR from Texas Instruments 2200:1 3000 230W UHP 3000/200W (Eco Mode) 2000/230W (Std Mode) 32dB (Eco Mode) 4:3 Native 16:9 Mode Min 2:1 - Max 2.4:1 115% 1.2 x Min 1.5 m - Max 10m Vertical + - 16deg 3.15kg 348w x 258d x 110h (mm) 100 - 240V (50 - 60 Hz)	INPUTS Composite S-Video Component Digital SCART Analogue PC RS232 Audio 1-4 OUTPUTS VGA Audio USB H Scan Rate V Scan Rate	RCA 4 Pin MINI DIN Via Adapter to VGA PC or Video DVI (HDCP Compliant) Via SCART Adapter to VGA 2 x VGA 3 pin MINI DIN Mini Jack Follows VGA Input Mini Jack Remote Mouse 15kHz - 100kHz 43Hz - 120Hz
---	---	---	---

