



## Key Features

- Truly portable - pocket-sized, lightweight and rechargeable
- VGA cable adapter included – connect to PCs and laptops to make an impact presentation on the go
- Stores up to 6000 pictures or 8 hours of video on 4GB of internal memory
- Project large images of up to 60" diagonal
- 2000:1 contrast ratio for detailed images
- LED light source lasts over 20,000 hours while producing excellent color



With the Optoma PK102 pocket projector, add pizzazz to your life with new ways to share content both cool and critical. Easily connects to your favorite personal media player and features 4GB of internal memory – enough to hold up to 6000 pictures or 8 hours of video. You can even display right from your laptop's VGA connection. Fitting in the palm of your hand, the truly portable, battery-operated PK102 is perfect for sharing photos, videos and other images wherever you go!

## Detail Specifications

**Display Technology**  
DLP

**Resolution**  
Native HVGA (480 x 320)

**Maximum Resolution**  
SVGA (800 x 600) through VGA Adapter

**Contrast Ratio**  
2000:1 (Full On/Full Off)

**Light Source**  
LED (RGB)  
Estimated at 20,000 Hours

**Throw Ratio**  
1.9:1 (Distance/Width)

**Projection Distance**  
10" to 102" (0.25 to 2.6m)

**Image Size (Diagonal)**  
6" to 60" (0.15 to 1.5m)

**Aspect Ratio**  
3:2 Native and 4:3 Compatible

**Battery**  
Li-ion Rechargeable (3.7V, 1100mAh)

**Battery Life**  
Up to 1.5 Hours

**Displayable Colors**  
100% NTSC Color Gamut

**Audio**  
One 0.5-Watt Speaker

**Computer Compatibility**  
SVGA, VGA, VESA, PC and Macintosh Compatible  
w/Included VGA Adapter

**Video Input Compatibility**  
NTSC, PAL, SDTV (480i), EDTV (480p w/Optional Component Video Adapter)

**Video File Compatibility**

XVid (M-JPEG, MPEG2, MPEG4, RMVB, RM, WMV, DivX Files are Converted Using Optoma Pico Video Encoder\*)

**Image File Compatibility**  
JPEG, BMP

**User Controls**  
Complete On-Screen Menu  
Adjustments in 10 Languages

**I/O Connectors**  
18-pin Universal Port, 2.5mm Jack AV Input (Composite Video and Stereo Audio-In), DC Input Jack

**Projection Method**  
Front, Rear, Upright, Inverted

**Weight**  
4.4 oz (124g) with battery  
3.2 oz (90g) without battery

**Dimensions (W x H x D)**  
2" x 0.67" x 4.17" (51 x 17 x 106mm)

**Noise Level**  
Silent (No Fans or Moving Parts)

**Operating Temperature**

41° to 95°F (5° to 35°C)

**Power Supply**

AC Input 100-240V,  
Auto-Switching, 50-60 Hz DC  
Output 5V/2A

**Power Consumption**

6 Watts (Maximum Run from  
Battery)

**Standard Accessories**

Power Adapter, Rechargeable  
Li-ion Battery, Universal to Male  
USB Cable, Standard A/V Cable  
(RCA to Mini-Jack), Universal to  
VGA Cable, Tripod Adapter,  
Bag

**Warranty**

1 Year Limited Parts and Labor,  
90 Days on Battery

**UPC**

796435 41 124 4