


Brilliant Large Screen Display



The Optoma PRO360W is the ideal projector for multiple usages in business and education. Featuring high brightness of 3000 ANSI lumens and a high contrast ratio of 3000:1, the PRO360W projects exceptional color quality. With an HDMI input and 3D capability, the PRO360W is ready to take on any presentation challenge.

3D content can be viewed with active LCD shutter glasses when the projector is connected to a computer with a compatible 3D graphics card. Please visit www.optoma.com for more information.

PRO360W FEATURES


- ❑ Native WXGA DLP® by Texas Instruments with BrilliantColor™ Technology
- ❑ Bright images and high contrast ratio – 3000 ANSI lumens and 3000:1 contrast ratio (full on/full off)
- ❑ Rapid power-on and shutdown – saving you time and money
- ❑ Filter-free design means low cost of ownership
- ❑ Protect your investment – control panel lock and password protection allow you to customize security settings
- ❑ Wide range of connectivity options: HDMI, VGA-in, VGA-out, s-video, composite video, stereo audio-in, stereo audio-out and RS-232

PRO360W | Multimedia Projector

Projection Distance/Image Size

Projection Distance (Feet)	Maximum Diagonal (Inches)	Minimum Diagonal (Inches)
6	55	50
8	73	67
10	91	83
12	110	100
14	128	117
16	146	133
18	164	150

Control Panel



Optional Accessories

Lamp:	BL-FU185A
Remote Control:	BR-3047N
Carrying Case:	BK-4006
Power Cord (1m):	BC-PUPIX01
Power Cord (11m):	BC-PUPIX01
HDMI Cable (5m):	BC-HMHMX05
Composite Cable (1.8m):	BC-COCOX02
VGA Cable (1.8m):	BC-VGVGX02
VGA Cable (5m):	BC-VGVGX05
VGA to Component Adapter:	BC-VGCRXY00
Ceiling Mount:	BM-5001U
92" Matte White 16:9 Manual Pull-Down Screen:	DS-9092PMG+

Specifications

Display Technology:	Single 0.65" DMD DLP® Technology by Texas Instruments
Resolution:	Native WXGA (1280 x 800)
Maximum Resolution:	UXGA (1600 x 1200)
Brightness (Typical):	3000 ANSI Lumens
Contrast Ratio:	3000:1 (Full On/Full Off)
Lamp Type:	200W UHP
Lamp Life (STD/Bright)*:	6000/3000 Hours
Throw Ratio:	1.55 to 1.7:1 (Distance/Width)
Image Size (Diagonal):	27.2" to 300" (0.58 to 7.62 m)
Projection Distance:	3.28' to 32.8' (1.0 to 10 m)
Noise Level (STD/Bright):	30dB/32dB
Remote Control:	IR Remote Control
Computer Compatibility:	UXGA, WXGA, SXGA+, SVGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible
Video Compatibility:	NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (720p, 1080i/p)
3D Compatibility:	120Hz Frame Sequential 3D for Resolutions Up to 720p, 60Hz Field Sequential 3D for Resolutions Up to 480i
Aspect Ratio:	16:10 Native, 16:9 and 4:3 Compatible
Projection Lens:	F=2.5-2.67, f=21.8-23.98 mm, 1.1x Manual Zoom and Focus
Offset:	115%
Monitor Loop Through:	D-Sub 15-Pin VGA Output (Functional in Both Normal and Standby Modes)
User Controls:	Complete On-Screen Menu in 23 Languages
Audio:	2-Watt Speaker
Keystone Correction:	± 40° Vertical
Vertical Refresh Rate:	24 to 85Hz, 120 Hz
Horizontal Scan Rate:	15.3 to 91.1 KHz
Power Supply:	AC Input 100-240V, 50-60Hz, Auto-Switching
Power Consumption:	247 Watts (Bright), 200 Watt (STD), <5 Watts (Standby-Active), <1 Watt (Standby-Eco)
Weight:	5 lbs (2.27 kg)
Dimensions (W x H x D):	11.28" x 3.98" x 7.6" (287 x 101 x 193 mm)
Operating Temperature:	41° to 104°F (5° to 40°C), 85% Max Humidity, Adjustable Fan Speed for High Altitude Application
Displayable Colors:	1.07 Billion
Projection Method:	Front, Rear, Ceiling Mount, Table Top
Uniformity:	85%
Security:	Kensington® Lock, Keypad Lock, Security Bar
I/O Connectors:	HDMI, VGA-In, VGA-Out, S-Video, Composite Video, Stereo Audio-In, Stereo Audio-Out and RS-232
Standard Accessories:	AC Power Cord, VGA to VGA Cable, Remote Control, Batteries for Remote, Carrying Case, Lens Cap, Multilingual CD-ROM User's Manual, Quick Start Card and Warranty Card
Optional Accessories:	HDMI Cable, Ceiling Mount, VGA to Component Cable, S-Video Cable, Composite Video Cable, RS-232 Cable and Panoview™ Series Screens
Warranty:	One Year Limited Parts and Labor, 90 Days on Lamp
UPC:	796435 41 664 5

www.optoma.com

*Lamp life is dependent upon many factors, including lamp mode, display mode, usage, environmental conditions and more. Lamp brightness can decrease over time.



All Specifications are subject to change without notice. ©2010 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments. All other names mentioned herein are property of their respective owners.