Proxima DP5500







Display Type	3 x LCD TFT Panel VGA 4/3 Liquid Crystal Display		
Ansi-Lumen	-	Lux (bei 203 cm Screen)	
Contrast	-	-	
Black Level	-	-	
Offset	-		
Resolution	VGA 640 x 480 307.200 Pixel		
Video Modes	PAL NTSC 3.58 / 4.43; SECAM		
Application	Stationary | Permanent installation in the training room and meeting room as well as the conference room. Very narrow picture width and rooms with very little light.		
Light Source	250W Metalldampf Lamp Articel Nr.: L84		
Light Life	2000 h.		
Operating Costs	-		
Focus	-		
Zoom	-		
Objective	F=3,0-3,8 f=46,5-74,4 mm		
Throw Ratio	-		
Audio	3W		
Connections	2 Computer video 2 TV video 2 Computer stereo audio 2 TV stereo audio RS232C control port Stereo audio out 1 RGB monitor out		
Ceiling Mounting	Yes		
Power	-		
Size WxHxD	-		
Operating Noise	-		
Weight	-		
Keystone	-		
Illumination	-		
Frequenz	-		
Foot-Lamberts	-		
	-		

PROXIMA DP5500

Features	■ Remote control with laser pointer und mouse control -
Status Data	- Discontinued (EOL) // Last update of the data: 2023-08-04
More Details	HCinema https://www.projector-database.com/pro/proximadp5500-en.html

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.