

SONY®

Data Projector
VPL-PX40/PX35



*a brilliant
performance
every time*

The Key to Smart Presentations

...the Sony VPL-PX40/PX35 Projector

Visuals

Leave a lasting impression. With its brightness of 3500 ANSI lumens and a high contrast level, the VPL-PX40 is the easy and effective way to view presentations in any environment or lighting condition. Its 3D Gamma Correction and 3D Digital Comb Filter features, plus an RGB Enhancer for RGB and DDE for video, combine to make pictures always look their best.*

**The Brightness of the VPL-PX35 is 2600 ANSI lumens.*

***ANSI lumens is a measurement unit defined by the National American Institute IT7.228. Since there is no uniform method of measuring brightness, specifications may vary among manufacturers.*

Audio

Complete the experience. An integrated stereo-speaker system delivers audio to support the presentation visuals for even greater impact.

Presentation Tools

A laser-pointer, mouse function and 4-times Digital Zoom – all included on the supplied remote-control unit – help to make presentations run smoothly and keep the audience enthralled.

The projector itself – the main presentation tool – goes virtually unnoticed, because of near-silent operation.

Flexibility

The broad installation capabilities of the VPL-PX40/PX35 enable the projector to be mounted on the ceiling or floor, or installed in a rear-projection system. Installation flexibility is further enhanced by the choice of two optional lenses. With the Direct Power On/Off Function the projector can be turned on or off quickly using a circuit-breaker switch on a switchboard, and, for added security, the VPL-PX40/PX35 incorporates a password-authentication system.

For Powerful Presentations ...the VPL-PX40/PX35



Picture Quality

High Brightness and Contrast

With a new optical system incorporating Sony LCD panels and a 265 W UHP lamp, the VPL-PX40 offers outstanding brightness of 3500 ANSI lumens, while the VPL-PX35 provides an impressive 2600 ANSI lumens. High quality images can be projected even in high ambient light conditions, producing an extremely highcontrast ratio.

High Resolution

By using three 0.99" XGA LCD panels the VPL-PX40/35 delivers clean and detailed reproduction of all images.



Digital Signal Processing

The VPL-PX40/PX35 achieves high picture quality with Sony original Digital Signal Processing technology. The VPL-PX40/PX35 provides digital signal processing by adopting a newly developed driver for the LCD panel that directly accepts digital signals; thus the projector is capable of projecting images with high accuracy.

Smart APA

Dot phase and image size or shift can be automatically adjusted to their optimal settings according to input signals.

3D Gamma Correction

The 3D Digital Gamma Correction circuit simultaneously provides superb grayscale reproduction and helps to improve overall picture uniformity.

Dynamic Detail Enhancer (DDE)

This unique Sony technology generates high quality images through the Interlace/Progressive conversion processor. Signals of film-originated sources converted through 2-3 and 2-2 pull down process are detected, resulting in extremely accurate image reproduction.

RGB Enhancer

For a crisper RGB image, the VPL-PX40/PX35 is equipped with an RGB Enhancer function. A simple adjustment provides heightened image quality to match any image source – whether text, photos, or graphics.

Presentation Effectiveness

4-times Digital Zoom

To help convey a clear message, the 4-times Digital Zoom function allows users to zoom in on any part of the projected image during a presentation.

Stereo Sound

Users can improve the impact and effectiveness of presentations with stereo audio output from the built-in stereo-speaker system.

Useful Remote-Control Unit

The supplied remote-control unit is equipped with keys to control various projector functions, for smooth, persuasive presentations every time. It has an integrated mouse function for point-and-click control of a USB-connected computer, and it can work as a laser pointer to direct the audience's attention and guide them through the presentation.



Input Versatility

Multiple Inputs

Using a built-in high-performance scan converter, the VPL-PX40/PX35 accepts a wide range of input signals: composite video, S-Video, Y/R-Y/B-Y, Y/PB/PR and RGB video, as well as analog and digital computer signals. A variety of DTV signals (480/60i, 575/50i, 540/60p, 480/60p, 575/50p, 720/60p, 720/50p, 1080/60i, and 1080/50i) are also fully supported, extending its potential even further.

DVI interface

The VPL-PX40/PX35 accepts digital signals directly thanks to its DVI interface.



Screen Size		80-inch	100-inch	120-inch	150-inch	180-inch	200-inch	250-inch	300-inch
a'	Minimum	3350	4130	4900	6070	7230	8000	9940	11880
		(132 1/8")	(162 5/8")	(193 1/8")	(238 7/8")	(284 5/8")	(315 1/8")	(391 3/8")	(467 5/8")
	Maximum	4140	5110	6080	7530	8990	9960	12380	14810
		(163")	(201 1/4")	(239 3/8")	(296 3/4")	(354")	(392 1/4")	(487 3/4")	(583 1/4")
x		b+693 (b+27 3/8")	b+846 (b+33 3/8")	b+998 (b+39 3/8")	b+1227 (b+48 3/8")	b+1455 (b+57 3/8")	b+1608 (b+63 3/8")	b+1989 (b+78 3/8")	b+2370 (b+93 3/8")
b		150/175/200/250/275/300mm (6, 7, 7 7/8, 9 7/8, 10 7/8, 11 7/8 inches) adjustable when using PSS-610							



Specifications

Model		VPL-PX40	VPL-PX35
Optical	Projection system	3 LCD panels, 1 lens projection system	
	LCD panel	0.99-inch p-Si TFT Sony LCD panel with Micro Lens Array 2,359,296 pixels (786,432 pixels x 3)	0.99-inch p-Si TFT Sony LCD panel 2,359,296 pixels (786,432 pixels x 3)
	Projection lens	Approx. 1.3 times zoom lens, F1.7 to 2.3, f37.6 to 48.8 mm	
	Lamp	265 W UHP Lamp	
	Screen coverage	40 to 300 inches (viewable area, measured diagonally)	
Signals	Light output	3500 ANSI lumens*	2600 ANSI lumens*
	Colour system	NTSC, PAL, SECAM, NTSC4.43, PAL-M, PAL-N (automatically/manually selected)	
	Resolution	Video: 750 TV lines, RGB: 1024 x 768 pixels	
	Acceptable computer signals	RGB (fH: 19 to 92 kHz, fV: 48 to 92 Hz (up to UXGA))	
	Acceptable video signals	15 kHz RGB/Component 50/60 Hz, Progressive component 50/60 Hz, DTV (480/60i, 575/50i, 480/60p, 540/60p, 575/50p, 720/60p, 720/50p, 1080/60i, 1080/50i), Composite video, Y/C video	
General	Speaker	Stereo speakers system 40 x 70 mm (1 5/8 x 2 7/8 inches) Max. 2W x 2	
	Power requirements	100 to 240 V, 50/60 Hz	
	Power consumption	Max. 365 W, Standby 6 W	
	Operating temperature	0 to 35°C (32 to 95°F)	
	Operating humidity	35 to 85%	
	Dimensions	420 (W) x 115 (H) x 316 (D) mm (16 5/8 x 4 5/8 x 12 1/2 inches)	
	Mass	Approx. 7.5 kg (16 lb 10 oz)	
Inputs/Outputs	Heat dissipation	1246 BTU	
	VIDEO IN	Composite Y/C IN Y C Phono type, 1.0 Vp-p ±2 dB sync negative, 75 Ω Mini DIN 4-pin 1.0 Vp-p ±2 dB sync negative, 75Ω Burst 0.286 Vp-p ±2 dB (NTSC), 75Ω or 0.3 Vp-p ±2 dB (PAL), 75Ω	
INPUT A	Analog RGB	HD D-sub 15-pin (female)	
	R	0.7 Vp-p ±2 dB positive, 75Ω	
	G	0.7 Vp-p ±2 dB positive, 75Ω	
	G with Sync	1.0 Vp-p ±2 dB sync negative, 75Ω	
	B	0.7 Vp-p ±2 dB positive, 75Ω	
	SYNC/HD		
	Composite sync	1.0 to 5.0 Vp-p, high impedance positive/negative	
	Horizontal sync	1.0 to 5.0 Vp-p, high impedance positive/negative	
	VD		
	Vertical sync	1.0 to 5.0 Vp-p, high impedance positive/negative	
INPUT B	AUDIO IN	Stereo mini jack, 500 mV rms, impedance more than 47 kΩ	
	Analog RGB	HD D-sub 15-pin (female)	
	R	0.7 Vp-p ±2 dB positive, 75Ω	
	G	0.7 Vp-p ±2 dB positive, 75Ω	
	G with Sync	1.0 Vp-p ±2 dB sync negative, 75Ω	
	B	0.7 Vp-p ±2 dB positive, 75Ω	
	SYNC/HD		
	Composite sync	1.0 to 5.0 Vp-p, high impedance positive/negative	
	Horizontal sync	1.0 to 5.0 Vp-p, high impedance positive/negative	
	VD		
INPUT C	AUDIO IN	Stereo mini jack, 500 mV rms, impedance more than 47 kΩ (Shared by INPUT B/C)	
	Digital RGB	DVI-D (TMDS)	
INPUT D	AUDIO IN	Stereo mini jack, 500 mV rms, impedance more than 47 kΩ (Shared by INPUT A/B/C)	
	Analog RGB/Component	5 BNC (Female)	
	R/R-Y	0.7 Vp-p ±2 dB positive, 75Ω	
	G	0.7 Vp-p ±2 dB positive, 75Ω	
	G with Sync/Y	1.0 Vp-p ±2 dB sync negative, 75 Ω	
	B/B-Y	0.7 Vp-p ±2 dB positive, 75Ω	
	SYNC/HD		
	Composite sync	1.0 to 5.0 Vp-p, high impedance positive/negative	
	Horizontal sync	1.0 to 5.0 Vp-p, high impedance positive/negative	
	VD		
USB	AUDIO IN	1.0 to 5.0 Vp-p, high impedance positive/negative	
	AUDIO IN	Stereo mini jack, 500 mV rms, impedance more than 47 kΩ	
OUTPUT	MONITOR OUT**	Up (female) x 1 (Shared by INPUT A/B/C/D)	
	AUDIO OUT (Variable out)	HD D-sub 15-pin (female) RGB: Gain Unity, 75Ω SYNC/HD, VD: 4.0 Vp-p (open), 1.0 Vp-p (75 Ω)	
REMOTE	RS-232C	Stereo mini jack, max. 1 V rms, when the input signal is 500 mV rms, impedance less than 5 kΩ	
	ETHERNET port	D-sub 9-pin (female) RJ-45: 10 BASE-T/100 BASE-TX	
CONTROL S IN/ PLUG IN POWER		Stereo mini jack	
		5.0 Vp-p, plug in power, DC 5V	
Safety regulations		UL, cUL, DHHS, FCC Class A, IC Class A, NEMKO, CE (LVD), CE (EMC), C-Tick, CCC, VCCI class B, JETTA	
Laser beam	Laser type	Class II	
	Wavelength	645 nm	
Supplied accessories	Output	1 mW	
	Remote commander, Monitor Cable (2 m): HD D-sub 15-pin to HD D-sub 15-pin, USB Cable A type to B type (2 m), AA size Battery (x 2), Lens Cap, Air Filter, Operating Manual, Installation Manual for dealers		

* ANSI lumens is a measuring method of the American National Standards Institute IT7. 228. Since there is no uniform method of measuring brightness, specifications will vary among manufactures. ** DIGITAL RGB and Component signals are not output from the MONITOR OUT terminal.

Input Signal Preset Data

No.	Preset Signal		fH (kHz)	fV (Hz)	H/V
1	VIDEO/60	60Hz	15.734	59.940	
2	VIDEO/50	50Hz	15.625	50.000	
3	480/60i		15.734	59.940	SonG/Y
4	575/50i		15.625	50.000	or
5	HDTV 1035/60i, 1080/60i		33.750	60.000	Composite
6*	640x350	VGA-1(VGA350)	31.469	70.086	P/N
7*		VESA 85(VGA350)	37.861	85.080	P/N
8*	640x400	NEC PC98	24.823	56.416	N/N
9*		VGA-2(TEXT)/VESA70	31.469	70.086	N/P
10*		VESA 85(VGA400)	37.861	85.080	N/P
11*	640x480	VESA 60	31.469	59.940	N/N
12*		Mac 13	35.000	66.667	N/N
13*		VESA 72	37.861	72.809	N/N
14*		VESA 75(IBM M3)	37.500	75.000	N/N
15*		VESA 85(IBM M4)	43.269	85.008	N/N
16*	800x600	VESA 56	35.156	56.250	P/P
17*		VESA 60	37.879	60.317	P/P
18*		VESA 72	48.077	72.188	P/P
19*		VESA 75(IBM M5)	46.875	75.000	P/P
20*		VESA 85	53.674	85.061	P/P
21*	832x624	Mac 16	49.724	74.550	N/N
22*	1024x768	VESA 43(8514)	35.524	86.958	P/P
23*		VESA 60	48.363	60.004	N/N
24*		VESA 70	56.476	69.955	N/N
25*		VESA 75	60.023	75.029	P/P
26*		VESA 85	68.677	84.997	P/P
27*	1152x864	VESA 70	63.995	70.019	P/P
28		VESA 75	67.500	75.000	P/P
29		VESA 85	77.487	85.057	P/P
30*	1152x900	SUN LO	61.795	65.960	N/N
31		SUN HI	71.713	76.047	Cneg(N/P)
32*	1280x960	VESA 60	60.000	60.000	P/P
33		VESA 75	75.000	75.000	P/P
34*	1280x1024	VESA 43	46.433	86.872	P/P
35		SGI-5	53.316	50.062	SonG(P/P)
36*		VESA 60	63.974	60.013	P/P
37		SXGA VESA75	79.976	75.025	P/P
38		SXGA VESA85	91.146	85.024	P/P
39	1600x1200	UXGA VESA60	75.000	60.000	P/P
43	480/60p (double frequency of NTSC)		31.470	60.000	SonG
44	575/50p (double frequency of PAL)		31.250	50.000	SonG
45	1080/50i		28.130	50.000	
47	720/60p		45.000	60.000	
48	720/50p		37.500	50.000	
50	540/60p		33.750	60.000	
52	1400x1050 SXGA+		63.981	60.020	N/N

When the signal other than ones in "Preset Signals" are input, the picture may not display correctly. When the aspect ratio of an input signal is other than 4:3, a part of the screen is displayed in black. The UXGA signal can be projected only when user set the frequency of a computer 60Hz. The digital input complies with the signals marked with asterisks(*) on the table. When the digital signal output from a computer is a signal other than the signals marked with asterisks(*) among the memory numbers 6 to 39, it is automatically output according to the specifications of the projector. The memory numbers 22 and 34 are the interface signals.

Optional Accessories

Projector Lamp

LMP-P260

(for replacement)



LMP-P260

Signal Cables

SMF-400

(HD D-sub 15-pin to 5 BNC, for RGB signal)

Optional Lenses

VPLL-FM22

(Fixed short-focus lens)


VPLL-ZM102

(Long-focus zoom lens)

Suspension Support

PSS-610

Dimensions



Unit :mm (inches)

Distributed by

Australia:
Ph: 1800 017 669
Or Visit www.sony.com.au/projectors
Sony Australia Limited
33-39 Talavera Road
North Ryde NSW 2113
Ph: 1800 017 669
Fax: 1800 117 669

New Zealand:
Ph: 0800 7669 776
Or email us at sonypro@sony.co.nz
Sony New Zealand Limited
Akoranga Business Park
Northcote Auckland
Ph: 0800 7669 776
Fax: (09) 488 0503

©2003 Sony Corporation. All rights reserved.
Reproduction in whole or in part without permission is prohibited.
Features and specifications are subject to change without notice.
All non-metric weights and measures are approximate.
Sony is a registered trademark of Sony Corporation.
Mac is registered trademark of Apple Computer, Inc.

Printed in Australia