

VPLSW630M

3100 lm WXGA Ultra Short Throw Projector w/o mount

$2,140.00

U.S.List Price

UPC: 027242871403

Overview

"The VPL-SW630projector is an ideal choice for teaching and training applications, with its 3100lumens WXGA Ultra Short Throw projection. The ultra short throw projection produces a 80"" diagonal wide image from only 19 inches away from the screen, which reduces glare from the projector even a presenter stands in front of the screen. Auto lamp dimming, max 8000h synchronized lamp and filter maintenance timing helps reduce total cost of ownership.
It is further packed with diverse features to meet demanding A/V needs. The variety of inputs allow the projector to fit a broad range of applications (inputs include; 2xRGB, HDMI, USB, Microphone inputs). High wattage 16W speaker eliminates the need for external speakers. Remote control of multiple projectors can be performed via a LAN (wired) network. Users can also project images over a wired LAN or a wireless network (an optional IFU-WLM3 wireless USB dongle is required for wireless connection). A USB Media Viewer allows users to directly project image files stored on a USB memory device."

Highlights

* 3100 lumens 3LCD Projector
* 2500:1 Contrast Ratio
* Native WXGA (1280 x 800) Resolution
* Ultra Short Throw Projection (0.27-0.29:1)
* Up to 8000h expected lamp life
* Versatile inputs including HDMI, 2xRGB, Mic Input
* RJ45 for network control and monitoring
* USB image viewer Function
* 1.05x Optical Zoom
* V : +/-4%, H : +/-2% Optical Lens Shift
* Equipped with Bright Era 3LCD Panels
* 12 bit 3D Digital Gamma Correction
* Auto Lamp Dimming Function
* Eco Mode for savings on energy
* Synchronized Lamp and Filter maintenance timing
* Designed to blend in visually
* Closed Captioning

Specifications

Optical Specifications	Detail
Color Light Output	3100 lumens (lamp mode : high), 2400 lumens (standard), 2000 lumens (low)
Light Output	3100 lumens (lamp mode : high), 2400 lumens (standard), 2000 lumens (low)
Contrast Ratio	3,000 :1
Lamp	High-pressure mercury lamp 225 W type
Lamp Life	3000H(lamp mode : High) / 5000H(Standard) / 8000H(Low)
Projection Lens	Zoom/Focus -Approx. 1.03x manual zoom / Manual focus Lens Shift - Manual, Vertical +/- 4% Horizontal +/- 2%
Throw Ratio	0.27 to 0.29:1

Screen Coverage	65" to 110

Input/Output Specifications	Detail
S-Video In	Mini DIN-4pin Audio : Pin jack x2 (shared with VIDEO IN)
Composite Video In	RCA phono jack, Audio : Pin jack x2 (shared with S VIDEO IN)
Analog RGB/Component In	Mini D-sub 15-pin (RGB) x1, Mini D-sub 15-pin (RGB/Y Pb Pr) x1 / Audio: Stereo mini jack
Digital In	HDMI (Digital RGB/Y Pb Pr, Digital Audio), HDCP Support
Network	RJ-45: 10Base-T / 100Base-TX, Optional wireless image transfer (IFU-WLM3)
Monitor Out	Mini D-sub 15-pin (from Analog RGB input)
Variable Audio Out	Stereo mini jack (variable out)
Remote Control	RS232C (D-sub 9pin)

Electrical Specifications	Detail
Color System	NTSC3.58, PAL, SECAM, NTSC4.43, PAL-M, PAL-N
Acceptable Computer Signals	Maximum display resolution : 1600x1200 dots
Acceptable Video Signals	Video(Composite), 15k(480/60i, 575/50i), DTV (480/60p, 575/50p, 720/60p, 720/50p, 1080/60i, 1080/50i, 1080/60p, 1080/50p)

General Specifications	Detail
Dimensions (W x H x D)	14 21/32" x 6 9/16" x 15 1/32"
Weight	13 lb 4 ozs
Power Requirements	Ac 100 to 240 V 3.3 to 1.5 amps 50hz/ 60hz
Power Consumption	323 Watts (120V)
Speaker	16W x 1 (monaural)

Other Specifications	Detail
Environmental Notice	Lamp in this product contains mercury. Disposal of these materials may be regulated due to environmental considerations. For disposal or recycling information, please contact your local authorities or the Telecommunications Industry Association (www.eiae.org).

Accessories

Optional Accessories

Model:	Description:	U.S.List Price
	Replacement lamp	Pricing available upon request
	USB Wireless LAN Module	Pricing available upon request

Resources

Product Manual

Description:	Release Date	Type/Size
45327691M.pdf		pdf / 4,523K

Brochure

Description:	Release Date	Type/Size
vpl-sw630brochure.pdf		pdf / 698K

This PDF was printed at sony.com/professional. Copyright 2011, Sony Electronics Inc All Rights Reserved.