TECHNICAL DATA UTAX DXL 5030

DISPLAY	
Technology	3 x 2 cm (0.7") p-Si with MLA LCD panels
Resolution (pixel)	1,024 x 768
IMAGE QUALITY	
Brightness	3,000 ANSI lumens
Contrast ratio	400 : 1
Projection lamp	200 W AC (152 W eco mode)
Lifetime of lamp (hrs.)	3,000*
OPTICAL SYSTEM	
Lens	F = 1.7 – 2.0, f = 24.0 – 28.8 mm, manual zoom / focus
Projection ratio	1.5 – 1.8 : 1
Image diagonal	0.63 – 7.62 m
Projection distance	0.71 – 10.9 m
COMPATIBILITY	
Horizontal frequency	15 – 100 kHz
Vertical frequency	50 – 120 Hz
Computer resolution	from VGA up to UXGA
Video	PAL, PAL-60, PAL-N, PAL-M, HDTV (1080i/720p), SECAM
INPUTS	
Computer	2 x Mini D-Sub, 1 x RS-232, 1 x PCMCIA (type II)
Video	1 x component (3 x cinch), 1 x S-video, 1 x cinch
Audio	2 x 3.5 mm mini jack, 2 x cinch (L/R)
Remote	-
OUTPUTS	
Computer	1 x Mini D-Sub, 2 x USB (type A+B)
Audio	1 x 3.5 mm mini jack
GENERAL	
Audio system	1 x 1 W stereo
Main voltage (50 – 60 Hz)	100 – 120, 200 - 240 V~
Power consumption max.	280 W, Standby: 6 W
Operation noise	35 dB (A) / 30 dB (A)*
Dimensions (h x w x d)	97 x 340 x 245 mm (without feet and lens)
Weight	3,6 kg
Certifications	CE, TÜV, GS
Remote control	3D reform control, auto picture adjustment, mute function, PC mouse control
Shipping content	projector, soft carrying case, remote control, Mini D-Sub signal cable, power cord, USB cable, lens cap, CD-ROM (PJ-user software and user manual)
Optional accessories	spare lamp, hardcase, ceiling and wall mountings, cables, projector stands

UTAX DXL 5030 – MOBILE SOLUTION FOR LARGE ROOMS

Flexibility in the business sector: With its extremely compact dimensions and its lightweight design, the DXL 5030 is one of the smallest LCD projectors with 3,000 ANSI lumens.



HIGHLIGHTS

- brightness: 3,000 ANSI lumens
- manual and automatic vertical keystone correction
- auto colour correction
- manual colour correction
- eco mode
- chalkboard function
- security function
- LAN function
- digital 3D reform geometric correction
- OSD in 19 languages
- help function
- PC card- and USB slot
- plug&play

* in eco mode



UTAX and the UTAX logo are registered trademarks of UTAX GmbH.
All other brand names are registered trademarks of their respective owners.
Subject to alterations and changes of product line, models, designs or features! (08/2005)