TECHNICAL DATA UTAX DXL 5032

DISPLAY	
Technology	3 x 2.54 cm (1.0") p-Si with MLA LCD panels
Resolution (pixel)	1,024 x 768
IMAGE QUALITY	
Brightness	3,200 / 2,600 / 1,900 ANSI lumens*
Contrast ratio	800 : 1
Projection lamp	275 W / 220 W /160 W*
Lifetime of lamp (hrs.)	2,000 / 3,000 / 4,000*
OPTICAL SYSTEM	
Lens	F = 1.74 – 2.18, f = 30.8 – 41.6 mm, motor zoom / focus
Projection ratio	1.5 – 2.1 : 1
Image diagonal	0.64 – 12.7 m
Projection distance	0.75 – 21.0 m
COMPATIBILITY	
Horizontal frequency	15 – 100 kHz
Vertical frequency	50 – 120 Hz
Computer resolution	from VGA up to UXGA
Video	PAL, PAL-60, PAL-N, PAL-M, HDTV (1080i/720p), SECAM
INPUTS	
Computer	1 x Mini D-Sub, 2 x PCMCIA (type II), 1 x RS-232, 1 x DVI-D, 2 x USB (type A+B)
Video	1 x component (5 x BNC), 1 x S-video, 1 x cinch
Audio	3 x 3.5 mm mini jack, 2 x cinch (L/R)
Remote	1 x 3.5 mm mini jack
OUTPUTS	
Computer	1 x Mini D-Sub, 1 x DIN 8pin (mouse), 1 x USB (mouse)
Audio	1 x cinch (L/R)
GENERAL	
Audio system	2 x 5 W stereo
Main voltage (50 – 60 Hz)	100 – 120, 200 - 240 V~
Power consumption max.	390 W, Standby: < 1 W
Operation noise	39 / < 34 / < 29 dB (A)*
Dimensions (h x w x d)	115 x 334 x 323 mm (without feet and lens)
Weight	5.9 kg
Certifications	CE, TÜV, GS
Remote control	Laserpointer and mouse control, 3D-reform control, source select, auto picture adjustment
Shipping content	projector, remote control, Mini D-Sub signal cable, power cord, USB mouse, lens cap, user manual, CD-ROM (PJ user software)
Optional accessories	spare lamp, longlife lamp, hardcase, ceiling and wall mountings, cable (e.g. DVI-D), wide angle and telezoom lens, projector stands

UTAX DXL 5032 – CONFERENCE ROOM PROJECTOR WITH LAN FUNCTION

When it comes to fixed installations for large-scale events, the DXL 5032 is your best bet for first class presentations, thanks to its wide range of connections and network options.



HIGHLIGHTS

- brightness: 3,200 ANSI lumens
- motorized zoom and focus
- LAN / WLAN functions
- digital 3D reform geometric correction
- chalkboard colour option
- sRGB
- 2 PCMCIA slots
- 4 security functions
- auto colour correction
- eco mode
- plug&play
- optional longlife lamp
- 2 optional lenses

* normal / in eco mode / with optional lamp XLS032 (longlife lamp)



UTAX and the UTAX logo are registered trademarks of UTAX GmbH.
All other brand names are registered trademarks of their respective owners.
Subject to alterations and changes of product line, models, designs or features! (08/2005)