

V7 PD725X

Productspecifications:

Display:	Digital Light-Processing DLP-Technology by Texas Instruments
Resolution:	Native: XGA (1024 x 768)
Computer Compatibility:	SXGA (1280 x 1024)
Video Compatibility:	PAL, SECAM, NTSC, HDTV
Aspect Ratio:	4:3 / 16:9 screen selectable
Contrast Ratio:	2000:1 (on/off)
Displayable Colours:	16.7 million colours
Brightness:	1.100 ANSI Lumens
Projection Lens:	f = 25.8 - 30.0 mm, F/2.8-3.1
Projection Screen Size:	0.7 m - 6.78 m (27.6" up to 267,2") diagonal
Throw Distance:	1.2 m - 10 m
Horizontal Scan Rate:	15 ~ 100 kHz
Vertical Refresh Rate:	43 ~ 120 Hz
Lamp Type:	120 Watts user replaceable P-VIP lamp
Lamp Life:	2000 hours
Keystone Correction:	vertical: +/- 16 degrees, horizontal: +/- 16 degrees
Audio:	
Weight:	0,95 kgs
Dimension:	198 x 148 x 57 mm (W x D x H)
Remote Mouse Control:	Remote control (credit card type)
Power Supply:	
Power Consumption:	190 W (max.), standby < 5W
Operating Temperature:	5°C - 35°C - max. humidity 80%
Noise Level:	34 dB (typ.)
Uniformity:	
Standard Accessories:	AC power cord 1.8 m, 15-Pin VGA to 15-Pin VGA cable 1.8 m, Component Video Adaptor (3x RCA for 15Pin D-Sub input), Composite Video cable 1.8 m, S-Video cable 1.8 m, Carry bag, Remote control (credit card type), Battery for remote control, Lens cap, Users guide, Quick-Start Guide, Warranty card, optional: ceiling mount kit
Warranty:	3 years Pick-Up Service, 90 days on lamp