Preliminary Product Specification
The Product Specification Might Change

EDUCATION PROJECTOR

D755WTi



WXGA ultra-short-throw projector with built-in interactivity and a host of connectivity options

The D755WTi is Vivitek's new compact ultra-short-throw projector with built-in interactivity function which make possible to turn any standard screen or white surface into an interactive projection solution. The D755WTi delivers high brightness with 3,000 ANSI Lumens and an outstanding contrast ratio of 5000:1 for a perfectly displayed image. The D795WTi is a stylish projector that is future proof with DLP-3D Ready capability, powerful 10Wx2 built-in speakers and an assortment of connectivity options include HDMI v1.3 for perfect digital image transmission and RJ-45 for network connectivity, the D755WTi is the ultimate education projector for perfect presentations.

Features

- DLP® and BrilliantColor™ technologies for sharp and detailed image quality
- Built-in IWB functionality with interactive pens
  - Dual pen support for simultaneous use
- Delivers a large 80" to 100" image from a ultra-short distance
  - Helps prevent shadow obstruction and light glare in the presenter's eyes
- Bright 3000 ANSI lumens with a colorful 5000:1 contrast ratio
- Energy efficient lamps that last up to 8000 hours (in economy mode)
- Network ready for integration and system administration via RJ45
- VGA–output for display on a secondary monitor
- Powerful 10Wx2 audio speaker
- Top-loading, cover for quick and easy lamp replacement
- Sealed optical engine, minimizing the impact of dust and smoke
- Keypad lock prevents accidental system adjustments

Product Pictures









Specifications	
Display Type	DLP
Brightness	3000 ANSI Lumens
Native Resolution	WXGA (1280 x 800)
Maximum Resolution	UXGA (1600 x 1200)
Contrast Ratio	5000 :1
Lamp Life and Type	5,000/8,000 Hours (Std./ Eco Mode) 230W
Image Size (Diagonal)	80"- 100"
Projection Lens	Manual Focus
Zoom Ratio	Fixed Lens
Aspect Ratio	16:10 Native
Throw Ratio	0.35:1
Offset	342mm-368.3mm (±50 mm)
Keystone Correction	Vertical ± 15° (±30 Step)
Horizontal Frequency	15, 30-91.4KHz
3D Ready	Yes (via DLP Link)
Vertical Scan Rate	43 - 87Hz
Speakers	10W (Mono) x2
Lens Shift Range	N/A
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	HDMI v1.3, VGA-In (x2), S-Video, Composite, Audio-In RCA, Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ45, 3D-Sync Out, RS-232C, USB (Service)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock
Dimensions (W x D x W)	288 x 374 x 127mm
Weight	5Kg
Noise Level	29dB/33dB (Eco / Normal Mode)
Power Supply	AC 100-240V, 50/ 60Hz
Power Consumption	260W (Eco Mode), 290W (Normal Mode), <0.5W (Standby Mode)
Warranty Education Warranty	3 Years, 1 Year (or 1,000h) on the Lamp 5-Year Warranty, 3-Year (or 2,000 hours)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Interactive Pen (x2), Documentation Kit
Optional Accessories	Replacement Lamp, Remote
UPC	TBC

© Copyright 2013 Vivitek. Vivitek is a registered trademark of Delta Electronics, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments. All specifications are subject to change at any time. Address: Vivitek EMEA, Zandsteen 15, 2132 MZ Hoofddorp, The Netherlands, Tel: +31 20 655 0960, Fax: +31 20 655 0999, E-Mail: info@vivitek.eu

© Copyright 2013 Vivitek. Vivitek is a registered trademark of Delta Electronics, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments. All specifications are subject to change at any time. Address: Vivitek EMEA, Zandsteen 15, 2132 MZ Hoofddorp, The Netherlands, Tel: +31 20 655 0960, Fax: +31 20 655 0999, E-Mail: info@vivitek.eu