# Vivitek D862

Bright XGA Digital Projector



## Product Features

- Bright 2800 ANSI lumens and high 2500;1 contrast ratio
- Native XGA (1024 x 768) resolution with a maximum resolution up to UXGA (1600 x 1200)
- DLP® and BrilliantColor™ technologies for sharp and detailed image quality
- Long lifetime lamp up to 6,000 hours
- DLP-Link 3D ready for amazing visuals
- Optical lens with a 1.2x zoom ratio
- Built-in audio speaker
- Security solutions include: Kensington® security slot, security bar, keypad lock

## Product Photos









## Product Specifications

| | |
|---|---|
| Display Type | DLP |
| Brightness | 2800 ANSI Lumens |
| Native Resolution | XGA (1024 x 768) |
| Maximum Resolution | Up to UXGA (1600 x 1200)@60Hz |
| Contrast Ratio | 2,500:1 |
| Lamp Life and Type | 4500 / 6000 Hours (Boost / Std. Mode), 190W |
| Throw Ratio | 1.6 - 1.92 : 1 |
| Image Size (Diagonal) | 25.6"-308" |
| Projection Distance | 1 - 10m (3.28ft - 32.8ft) |
| Projection Lens | F=2.50~2.72, f = 17.81~21.35mm |
| Zoom Ratio | 1.2X |
| Aspect Ratio | 4:3 Native, 16:9 Compatible |
| Offset | 128% +/-10% |
| Keystone Correction | Vertical +/- 15° (+/- 30 Step) |
| Horizontal Frequency | 15, 30-90KHz |
| Vertical Scan Rate | 43 - 85Hz |
| 3D Ready | Yes |
| Speakers | 10W (Mono) |
| Video Compatibility | SDTV(480i), EDTV (480p), HDTV (720p, 1080i), NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM |
| I/O Connection Ports | HDMI 1.3V (x2), VGA-In, S-Video, Composite Video, Audio-In RCA (L/R), Audio-In (Mini-Jack), Audio-Out (Mini-Jack), RS-232C, USB (Service) |
| Projection Method | Table Top, Ceiling Mount (Front or Rear) |
| Security Solutions | Kensington® Security Slot, Security Bar, Keypad Lock |
| Dimensions (W x D x W) | 280 x 260 x 113 mm (11.02" x 10.23" x 4.44") |
| Weight | 2.7Kg (6 lbs) |
| Noise Level | 35dB/32dB (Std. / Boost Mode) |
| Power Supply | AC 100-240V, 50/60Hz |
| Power Consumption | 260W (Boost Mode), 230W (Std. Mode), <0.5W (Standby Mode) |
| Standard Accessories | AC Power Cord, VGA Cable, Carrying Case, Remote Control, Lens Cap, Documentation Kit |
| Optional Accessories | Replacement Lamp, Remote, Carrying Case |

©2011 Vivitek Corporation. Vivitek is a trademark of Vivitek Corporation. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subjection to change without prior notice.

Vivitek Corporation 1F, No. 186, Ruey Kuang Road, Neihu Dist., Taipei, Taiwan, R.O.C www.vivitekcorp.com