

PRO-85

0.65" DLP®, 4000 ANSI, Ultra Short Throw 2D/3D Projector

The exciting Wolf Cinema PRO-85 ultra-short throw projector is ideal for use in corporate boardrooms, in churches, classrooms – and especially in home theaters where space is at a premium. With the precision 0.25:1 lens, you can project a 100" image from just 21.5" [55cm] away! This enables you to place the projector very close and just above or below the screen, providing terrific 1080p viewing from every seat in the house. Enjoy excellent 2D/3D imaging [3D glasses and RF emitter sold separately], plus simplified system operation via IR, RS232 and LAN control.

The projector can be simply placed on a table top, or attached to the optional wall mounting bracket [as shown], accessory part number WC-PM-PRO85. The wall mount incorporates an adjustable arm extension and mounting plate, and provides for a wide range of roll, pitch and yaw adjustment capabilities.

Specifications:

Imaging Technology	0.65" DarkChip3 1080p DLP® Technology by Texas Instruments
Brightness	4000 ANSI Lumens
Contrast	20,000:1
Throw Factor/Offsets	0.25:1, Fixed. Vertical Offset: 118%
Keystone Correction	± 20° Vertical
Lamp Type and Life [hrs]	260W; Est. lamp life 6500 (Eco+) / 5000 (Eco) / 3000 (Bright)
Noise Level (Eco mode)	28dB
Audio	16-Watt speaker [1]
Computer Compatibility	UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Video Compatibility	PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p, 1080p)
Input Scanning Frequency	H-sync. 15.3 - 91.1kHz; V-sync. 24 - 85Hz (120Hz for 3D)
Video I/O	HDMI 1.4a with 3D support [2], VGA - YPbPr/RGB [2], VGA output [1, shared with VGA 2], Composite video input
Audio I/O	Stereo 3.5mm Mini-RCA audio input [2], 3.5mm Mini-RCA audio-output, 3.5mm Mic Input
Control, Other I/O	12V Mini-RCA trigger, RS-232C D-sub 9 pin, RJ-45, USB-A [Power Only], USB remote mouse/service, 3D Sync
Dimensions (W x H x D)	15.15" x 3.89" x 12.20" (385 x 99 x 310mm)
Weight	10.5 lbs (4.78 kg)
Operating Temperature	41-104°F (5-40°C), 85% max humidity
Voltage	AC Input 100-240V, 50-60Hz, auto-switching
Power Consumption	310W Bright mode / 260W Eco mode (< 0.5W Standby)
Supplied Accessories	AC Power Cord, IR Remote Control, AAA Batteries [x 2], VGA Cable, User manual CD-ROM

Optional Accessories:

WC-PS-03	ProScaler MK III Video Processor with E-VariScope™ Technology
WC-SD3PK-04	3D starter pack: includes RF emitter and 2 (two) sets of Active 3D Shutter Glasses
WC-SD3DA-04	Active 3D Shutter Glasses, RF
WC-PM-PRO85	Custom Ultra-Short Wall Mount, Adjustable
WC-LPU85	Replacement 260W UHP Lamp Assembly



WC-PM-PRO85
Ultra-Short Wall Mounting System
(Sold Separately)

*Features and specifications subject to change without notice.
DLP is a registered trademark of Texas Instruments. VariScope and E-VariScope are trademarks of Wolf Cinema.*